


NewNight® LED-Ground Recessed Luminaire LS12T

Path and orientation lighting - object lighting

Information

LED-Ground Recessed Luminaire
Bezel made of stainless steel
Optical cover toughened safety glass(12mm)
Directed light provided by lens optic
Various light distributions from the optics series ME
Highest efficiency of all system components - LongLIFE
Integrated LED control gear incl. surge protection 4K



Technical Informations

Betriebsgeräte:	ENEC interface 1-10V
Breite:	270 mm
Farbtemperaturen:	3000K, 4000K, 1800K, 2700K, 3500K
Gehäuse:	Aluminum, incl. installation sleeve made of polyamide
Höhe:	210 mm
IP :	67
Länge:	230 mm
Lebensdauer:	L80B50 > 50.000h
Leistungsaufnahme :	15 Watt
Lichtstrom:	1156lm 1233lm 1523lm 1585lm 1632lm
Schaltfunktionen:	on/off
Schutzklasse :	SK I

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the product conforms to European EMC regulations.

BRAUN Lighting Solutions
Nunsdorfer Ring 2-10
12277 Berlin
Germany

 www.braun.lighting
 info@braun-lighting.com
 +49 (0)30 7 007 763-100
 +49 (0)30 7 007 763-101



NewNight® LED-Ground Recessed Luminaire LS12T

Path and orientation lighting - object lighting

Technische Informationen :	Bezel made of stainless steel, round, brushed and pasivated Optical cover toughened safety glass (clear), 12mm thick (hardened) Load capacity: up to 2.5 t per wheel Wiring: incl. cable; 3 x 1,5mm ² (L=0,5 Mtr.)
Verwendung:	Path and orientation lighting - object lighting
Zulässige Betriebsspannung:	90-305VAC
Zulässige Umgebungstemperatur:	- 40°C up to 50°C

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the product conforms to European EMC regulations.

BRAUN Lighting Solutions
Nunsdorfer Ring 2-10
12277 Berlin
Germany

 www.braun.lighting
 info@braun-lighting.com
 +49 (0)30 7 007 763-100
 +49 (0)30 7 007 763-101

