

Gas-Pendant Light 4

Information

The LED pendant lamp 4 is a faithful reconstruction of the A-6 model. Due to its rotationally symmetrical light distribution, this lamp is ideally suited for the illumination of squares, streets, residential areas, green spaces and driveways. The luminaire is equipped with energy-efficient innovative LED technology.

Choose between golden-yellow lighting that makes the surroundings appear lively and natural, or very bright safety lighting with convincing light quality.



His.lux® LED-Modul Serie 333



TECHNISCHEN DATEN

Modulleistung	6 - 36 Watt
Lebensdauer	>60.000 Std.
Farbtemperatur	2700K*
Lichtstrom	2225 lm (36 Watt)
Farbwiedergabe	CRI > 85
LED-Raum	IP 65
historical diffuser	PC satiniert
Einsatzbereich	-40°C bis +55°C
Schutzklasse	I oder II

*Farbtemperaturen frei wählbar

NewNight® Kegel LED-Modul



TECHNISCHEN DATEN

Modulleistung	8 - 25 Watt
Lebensdauer	>60.000 Std.
Farbtemperatur	4100K*
Lichtstrom	2620 lm
Farbwiedergabe	CRI > 85
LED-Raum	IP 65
LED-Abdeckung	PC glasklar oder satiniert
Einsatzbereich	-40°C bis +55°C
Schutzklasse	I oder II

*Farbtemperaturen frei wählbar

Technical Informations

Befestigungsschnittstelle :	G1/2 inch external thread
Breite:	382 mm
Gehäuse:	Made of weather-resistant natural aluminum
Gewicht:	ca. 7 kg
Glasglocke :	On request and at extra cost, paint finishes according to the RAL color table and special FerroGrip paint finishes are possible.
Höhe:	632 mm
Länge:	382 mm
Leuchtenkörper :	galvanized or hot-dip galvanized steel
Reflektor:	powder-coated according to RAL 901

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the product conforms to European EMC regulations.

BRAUN Lighting Solutions
Nunsdorfer Ring 2-10
12277 Berlin
Germany

www.braun.lighting
info@braun-lighting.com
+49 (0)30 7 007 763-100
+49 (0)30 7 007 763-101






Gas-Pendant Light 4

Schalt- und Steuergerätvarianten :	PlugBox: on/off PlugBox ESS Basic: manual adjustability of basic brightness PlugBox ESS Light: manual adjustability of basic brightness manual adjustability of reduced brightness, switching from basic brightness to reduced brightness over 230VAC control input, (twilight switching / phase cut-off) Interface: 230VAC MaxiDimm3000: manual adjustability of basic brightness manual adjustability of reduced brightness, switching from basic brightness to reduced brightness over 230VAC control input (twilight switching / phase cut-off) variable dimming or segment switch off for symmetric or asymmetrical light distribution, Interface: 230VAC 1-10V
Scharniere und Verschlusssteile :	Stainless steel or galvanized sheet steel
Sonstige Leuchtenbauteile :	galvanized or hot-dip galvanized steel
Verteilungskammer Flammen :	4
Zubehör:	

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the product conforms to European EMC regulations.

BRAUN Lighting Solutions
Nunsdorfer Ring 2-10
12277 Berlin
Germany

 www.braun.lighting
 info@braun-lighting.com
 +49 (0)30 7 007 763-100
 +49 (0)30 7 007 763-101

