
## **Plugbox On-Off**

## Information

The Plugbox On/Off is a connection aid device for several LED modules (up to 4 modules) that are to be connected in series.




## **Technical Informations**

Anmerkungen :	The reproduction, modification and commercial use of this document or parts of this document without the written consent of BRAUN Lighting Solutions e.K. is prohibited. BRAUN Lighting Solutions e.K. excludes any liability for damage to the unit, as well as consequential damages applicable by unsuitability, improper construction or intervention in the system, incorrect operation and usage as well as non-compliance with safety regulations. All data are known in the art at the time of the draft of this document. Changes, thereby resulting deviations from this data sheet through innovations, technology improvement or modification are reserved. For mistakes and printing errors, we assume no responsibility.
Anschluss Informationen:	All connections are designed as multi-pin plug connections, whereby all lines on the plug system must be connected via screw connections.  There is a 10-pin connector strip to which up to 4 LED modules as well as the power supply lines coming from the power supply unit can be connected. The pin assignment is shown in the following overview. If not all LED module connections are used, the not connected module must be replaced by a short circuit bridge to close the circuit (all LEDs are connected in series).  Example: If the LED module 2 from Table 1: Pin assignment is not used, a shorting bridge must be fitted to terminals 5 and 6. The parameters (e.g. minimum and maximum output voltage and thus number of LEDs) of the power supply unit used must be observed.

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the productconforms to European EMC regulations.








+49 (0)30 7 007 763-101



## **Plugbox On-Off**

maximaler Leitungsquerschnitt für Anschlüsse:

2,5 mm<sup>2</sup>



Anschluss	Funktion
1	vom Netzteil (+)
2	Vom Netzteil (-)
3	LED-Baugruppe 1 (+)
4	LED-Baugruppe 1 (-)
5	LED-Baugruppe 2 (+)
6	LED-Baugruppe 2 (-)
7	LED-Baugruppe 3 (+)
8	LED-Baugruppe 3 (-)
9	LED-Baugruppe 4 (+)
10	LED-Baugruppe 4 (-)

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the productconforms to European EMC regulations.

