## **Gas-Pendant Light 4**


## Information

The gas pendant lamp 4 is a faithful reconstruction of the A-6 model. This gas lamp achieves an excellent illumination, with a highly brilliant and natural color rendering. This golden-yellow illumination makes the surroundings appear lively and natural. High quality materials guarantee its longevity. The lamp is very easy to maintain due to a hinged maintenance opening and a fold-down glass dome. Due to its rotationally symmetrical light distribution, this luminaire is ideally suited for the illumination of squares, streets, residential areas, green spaces and driveways.





BS-GC Solar



## **Technical Informations**

| Befestigungsschnittstelle :      | G1/2 inch external thread   |
|----------------------------------|---|
| Breite:                          | ca. 382 mm  |
|                                  |   |
| Gasverbrauch:                    | at constant operating pressure of 24 mbar: 0.1 m <sup>3</sup> /h  |
| Gehäuse:                         | Made of weather-resistant natural aluminum  |
| Gewicht:                         | ca. 7 kg  |
| Glasglocke :                     | borosilicate glass; Execution: open at the mouth On request and at extra cost, paint finishes according to the RAL color table and special FerroGrip paint finishes are possible. |
| Höhe:                            | ca. 632 mm  |
| Reflektor:                       | Sheet metal, enamelled, white   |
| Scharniere und Verschlussteile : | Stainless steel or galvanized sheet steel   |
| Sonstige Leuchtenbauteile :      | galvanized or hot-dip galvanized steel  |
| Verteilungskammer   Flammen :    | 4   |
| Vorbereiteter Gasglühkörper :    | Socket 1562   |
| Zubehör:                         |   |

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the productconforms to European EMC regulations.

BRAUN Lighting Solutions Nunsdorfer Ring 2-10 12277 Berlin Germany www.braun.lightinginfo@braun-lighting.com

**(** +49 (0)30 7 007 763-100

10)30 7 007 763-101



## **Gas-Pendant Light 4**

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the productonforms to European EMC regulations.

BRAUN Lighting Solutions Nunsdorfer Ring 2-10 12277 Berlin Germany www.braun.lighting
info@braun-lighting.com
+49 (0)30 7 007 763-100
+49 (0)30 7 007 763-101

